

Distributed by: Laguna Clay Company 14400 Lomitas Ave City of Industry, CA 91746 1-800-4Laguna info@lagunaclay.com www.lagunaclay.com

Ferro Corporation Performance Pigments & Colors 251 West Wylie Ave. Washington, PA 15301 USA

Emergency telephone number CHEMTREC: 1-800-424-9300

CHEMTREC (outside U.S.): 1-703-527-3887

Phone Number: 1-724-223-5900

Date of Preparation: 03/08/2012

# MATERIAL SAFETY DATA SHEET

V-9118 BRT GLDN YELLOW 25 KGS **Product Name:** 

BAGS

Inorganic Pigment Chemical Family:

**Chemical Name:** Rutile, antimony chromium buff

**Synonym** Pigment Brown 24.

CAS-No.: 68186-90-3 77310 C.I. Number: 1108455 Product Code:

#### 2. HAZARDS IDENTIFICATION

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### **Emergency Overview**

Caution

Avoid dust formation. Do not breathe vapours/dust, May cause respiratory tract, eye and skin irritation. May cause physical irritation.

		HMI2	NFPA 704
Color: Yellow	Health:	1*	1
Physical Powder	Flammability:	0	0
state:	Physical Hazard:	0	0
Odor: Odorless	i ilyolodi iluzuru.	Ε	

#### **Potential Health Effects**

Principle routes of exposure: Inhalation, ingestion, skin and eye contact.

Eye contact: May cause slight irritation.

Skin contact: Prolonged skin contact may cause skin irritation.

May cause irritation of respiratory tract. Inhalation:

Ingestion: May irritate digestive tract.

Chronic toxicity: No known effects under normal conditions of use. Excessive inhalation of dust may cause

chemical pneumonitis, cyanosis, and pulmonary edema. Chronic inhalation exposure can

cause lung damage.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Weight %
Chrome antimony titanium buff	68186-90-3	100%

The mixed metal oxide pigment in this product is made by high temperature fusion. Due to resulting unique structure, the fired pigment will not necessarily exhibit the same properties as the component oxides or metals in their pure state.

## 4. FIRST AID MEASURES

Rinse immediately with plenty of water, also under the eyelids. Get medical attention if irritation Eye contact:

develops.

Laguna Clay Company 1-800-4Laguna info@Lagunaclay.com www.Lagunaclay.com

Product name: V-9118 BRT GLDN YELLOW 25 KGS BAGS

Skin contact: Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing

before re-use. If symptoms persist, call a physician.

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.

Ingestion: Drink plenty of water. Do not induce vomiting. Consult a physician if necessary.

Notes to physician: Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Flash point (°C): Non combustible

Suitable extinguishing media: Use extinguishing measures that are appropriate to local circumstances and the surrounding

environment. The product itself does not burn.

Hazardous decomposition products: Metal fumes.

Special protective equipment for

101

As in any fire, wear self-contained breathing apparatus (pressure-demand, NIOSH approved or

equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Evacuate area of all unnecessary personnel. Avoid dust formation. Do not breathe vapors/dust.

Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do

not flush into surface water or sanitary sewer system. Do not allow material to contaminate

ground water system.

**Methods for cleaning up:**Wear personal protective equipment. Sweep up and shovel into suitable containers for

disposal. Dispose of promptly. Clean contaminated surface thoroughly.

## 7. HANDLING AND STORAGE

## Handling:

firefighters:

Handle in accordance with good industrial hygiene and safety practice. Avoid dust formation. Do not breathe vapours/dust. Use only in area provided with appropriate exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not take internally. Do not eat, drink, or smoke in areas of use or storage. Wash thoroughly after handling.

#### Storage:

Keep container tightly closed in a dry and well-ventilated place. Store in original container.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure limits**

No TLV assigned. Minimize exposure in accordance with good hygiene practice.

Engineering measures: Provide appropriate exhaust ventilation at machinery and at places where dust or fumes can

be generated. Ensure that eyewash stations and safety showers are proximal to the work-

station location.

Eye protection: Safety glasses with side-shields.

Skin and body protection: Lightweight protective clothing. Remove and wash contaminated clothing before re-use. Keep

working clothes separately.

Hand protection: Impervious gloves. Follow the recommendations given by the manufacturer of protective

gloves.

Laguna Clay Company www.Lagunaclay.com 1-800-4Laguna info@Lagunaclay.com

Product name: V-9118 BRT GLDN YELLOW 25 KGS BAGS

Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment . NIOSH-approved

respirators should be worn where engineering controls and work practices do not reduce exposure to or below the PEL. Seek professional advice prior to respirator selection and use.

Hygiene measures: Wash hands before breaks and at the end of workday. Contaminated work clothing should not

be allowed out of the workplace. Ensure that eyewash stations and safety showers are

proximal to the work-station location.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Color: Yellow Physical state: Powder

Odor: Odorless Molecular weight: No data available No data available No data available Boiling point/range (°C): :Hq Melting point/range (°C): No data available Specific gravity (Water =1): No data available Vapor density: Non-volatile Vapor pressure : No data available

Evaporation Rate (Water = 1) Non-volatile Water solubility: Insoluble

VOC content (%) 0

#### 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Polymerization Will not occur.

Hazardous decomposition products: None under normal use. Metal fumes.

Materials to avoid: None known.

Conditions to avoid None known.

## 11. TOXICOLOGICAL INFORMATION

Acute toxicity: Information given is based on data on the components and the toxicology of similar products

Carcinogenic Effects: Not listed by IARC, NTP or OSHA as a carcinogen.

Target Organ Effects: Chromium compound (inorganic): Eyes, skin, respiratory system. Antimony: lungs, respiratory

system.

Component information, if any, is listed below

Chrome antimony titanium buff

LD50s and LC50s: Oral LD50 (Rat) = 10000 mg/kg

## 12. ECOLOGICAL INFORMATION

Aquatic toxicity: No data is available on the product itself. Information given is based on data on the

components and the ecotoxicology of similar products.

Chrome antimony titanium buff

Ecotoxicity - Fish Species Data:

96 h LC50 (Leuciscus idus) = 10000 mg/L static

Persistence and degradability: Not determined

#### 13. DISPOSAL CONSIDERATIONS

Waste from residues / unused

products:

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Where possible recycling is preferred to disposal or incineration.

#### 14, TRANSPORT INFORMATION

DOT (U.S.)

Laguna Clay Company www.Lagunaclay.com 1-800-4Laguna info@Lagunaclay.com

## 14. TRANSPORT INFORMATION

Proper shipping name: Not regulated.

TDG (Canada)

Proper shipping name: Not regulated.

#### 15. REGULATORY INFORMATION

#### U.S. Regulations:

TSCA: Not subject to TSCA 12(b) Export Notification

#### **SARA 313:**

Components	U.S CERCLA/SARA - Section 313 - Emission Reporting
Antimony compounds (10 - 20%)	1.0 % de minimis concentration
Chromium (III) compounds (5 - 10%)	1.0 % de minimis concentration

## State Regulations

This product or its ingredients have been evaluated for New Jersey, Pennsylvania, and California Prop 65 supplier notification requirements. Substances that are subject to notification requirements, if any, are listed below.

Components	PARTK:
Antimony compounds	Listed (PARTK)
Chromium (III) compounds	Listed (PARTK)

Components	NJRTK:
Antimony compounds	Listed (NJRTK)
Chromium (III) compounds	Listed (NJRTK)

# Canadian WHMIS

WHMIS hazard class: Non-controlled

Canadian Ingredient Disclosure List (IDL):

Canadian ingredient disclosure List (IDL):	
Components	Canada - WHMIS Ingredient Disclosure:
Antimony compounds	1
Chromium (III) compounds	0.1

#### International Inventories

TSCA 8(b): Listed or exempt.

Canadian DSL/NDSL list All ingredient(s) are listed on the DSL or NDSL

EC-No. Listed or exempt.

Philippines (PICCS): Listed.

Japan (ENCS): Listed or exempt.

Korea (KECL): Listed.
China (IECS): Listed.
Australia (AICS): Listed.
New Zealand (NZIoC): Listed.

## 16. OTHER INFORMATION

For Industrial Use Only.

Prepared by: Ferro Technical Center

Laguna Clay Company www.Lagunaclay.com 1-800-4Laguna info@Lagunaclay.com

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guaranty or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any applicable federal or state laws.

# **End of Safety Data Sheet**



Distributed by: Laguna Clay Company 14400 Lomitas Ave City of Industry, CA 91746 1-800-4Laguna info@lagunaclay.com www.lagunaclay.com